



MAR-CON - Wire Belt -

Head Office

sales@marconwirebelt.com
604-278-8922
1-877-962-7266

North American Sales

Ken Docktor
ken.docktor@marconwirebelt.com
209-968-0669

Date: _____

Rev.: _____

Company: _____

Contact Person: _____

Phone: _____ E-mail: _____

DOUBLE PITCH CHAIN DRIVEN BELT SPECIFICATION FORM

Overall Width: _____

Chain Center: _____

Mesh Width: _____

Rod Pitch: _____

Wire Diameter: _____

Spiral Pitch: _____

of Spirals in 12" W: _____

Crimp Wire Diameter: _____

Rod Diameter: _____

Ends Turned Down: ☐ Yes ☐ No

☐ Oversize Roller

☐ Standard Roller

of Spirals in 12" L: _____

Rods through pin of chain?: ☐ Yes ☐ No

Chain Pitch: _____

Rod End: ☐ Washer Weld ☐ Weld to Chain

Rods through connector link of chain?: ☐ Yes ☐ No

NOTES:
(I.E. SIDE PLATES, FLIGHTS,
OVERSIZED RODS ETC.)

TOLERANCE UNCLES OTHERWISE SPECIFIED

DECIMAL: .X ± .03
.XX ± .015
.XXX ± .005
.XXXX ± .0005

FRACTIONAL: ± 1/16

ANGULAR: ± 1/2°

* ALL DIMENSIONS ARE INCHES UNLESS
OTHERWISE SPECIFIED

* THIS DRAWING IS INTENDED SOLELY FOR
LAYOUT PURPOSES. IT IS THE RESPONSIBILITY
OF THE CUSTOMER TO RELAY ANY IMPORTANT
INFORMATION REGARDING ANY AND ALL DESIGN
FEATURES OF DESIRED BELT.

